


## SIZE CHART:

Rubber mounted head											
Model	D(mm) Diameter	H(mm) Height	d(mm) Shank diameter		h/mm Shank Length	Grit Size(#)	Package (pcs/bag)	Speed of revolution (rpm)	Graph 3D drawing		
			3	6							
X03103	3	10	▪		30	60-1500	100	25000			
X04133	4	13	▪		30						
X05153	5	15	▪		30						
X06173	6	17	▪		30						
X08203	8	20	▪		30						
X10203	10	20	▪		30						
X10206	10	20		▪	35						
X10256	10	25		▪	35						
X12203	12	20	▪		30						
X12206	12	20		▪	35						
X12256	12	25		▪	35						
X16256	16	25		▪	35						
X20033	20	3	▪		30						
X20043	20	4	▪		30						
X20053	20	5	▪		30						
X20256	20	25		▪	35						
X25033	25	3	▪		30						
X25043	25	4	▪		30						
X25053	25	5	▪		30						
X25256	25	25		▪	35						
X30066	30	6		▪	35						
X30086	30	8		▪	35						
X30106	30	10		▪	35						
X30256	30	25		▪	35						
X40066	40	6		▪	35						
X40086	40	8		▪	35						
X40106	40	10		▪	35						
							General:				
							60				
							80				
							120				
							180				
							240				
							320				
							400				
							600	50			
							Non standard customization:				
							800	10			
							1500	50			
								100			
								40			
								50			
									Model number: HDXHXd		

Other dimensions custom please visit [www.kytools.cn](http://www.kytools.cn) or send to [beibei.liu@kytools.cn](mailto:beibei.liu@kytools.cn)

## DETAILED DESCRIPTION:

- ▶ **Raw material:** Alumina
- ▶ **Particle size:** 60#、80#、120#、180#、240#、320#、400#、600#、800#、1500#
- ▶ **Shape:** Cylindrical, T-shaped, conical, spherical
- ▶ **Shank diameter:** 3mm、6mm、3.175mm、6.35mm
- ▶ **Handle length:** 30mm、35mm (other sizes can be customized)
- ▶ **Hardness of grinding head:**

High elastic grinding head, adjustable hardness (customizable) This product has a variety of specifications and granularity, accept non-standard size customization, range including height, aperture, material, handle length, etc. The most prominent features of this series of products are soft polishing and fine polishing. Can cooperate with various high speed electric tools or pneumatic tools. It is mainly used



for edge honing of carbide tools to remove fine burr from various materials. And widely used to remove resin mold burn marks, scales, rust, scratches, dents and chuck marks cleaning treatment; Also suitable for removing paint, electroplating and coating, by adjusting the high elasticity of rubber material, thus preventing machining scratches.

## PARTICLE SIZE GUIDE:

Particle size	60	80	120	180	240	320	400	600	800	1500
color										
	Purple	red	green	bean sauce	blue	gray	brown	light	yellow	cyan

